

ABB MEASUREMENT & ANALYTICS | INFORMATION | INF15/174-EN REV. A

ControlMaster CM15 and CMF160 Controllers and indicators CUS basic configuration sheet

1 Introduction

This Information sheet should be completed when a basic CUS configuration of a ControlMaster product is required. This sheet is applicable to the following products: CM15 and CMF160.

2 Configuration sheets

2.1 Application temlate

2.2 Level Parameters

Specific Gravity	
Volume Constant	
Volume Units	

2.3 Analog Input 1

Input Type	
Electrical Range Low	
Electrical Range High	
Engineering Range Low	
Engineering Range High	
Engineering Units	
Broken Sensor Drive	

2.4 Alarm 1

Туре	
Тад	
Source	
Trip	
Hysteresis (Units / Time)	

2.5 Totalizer 1

Туре	
Source	
Direction	
Units	
Stop / Go Source	
Reset Source	
Cut off	

2.6 Analog Input 2

Input Type	
Electrical Range Low	
Electrical Range High	
Engineering Range Low	
Engineering Range High	
Engineering Units	
Broken Sensor Drive	

2.7 Alarm 2

Туре	
Тад	
Source	
Trip	
Hysteresis (Units / Time)	

2.8 Totalizer 2

Туре	
Source	
Direction	
Units	
Stop / Go Source	
Reset Source	
Cut off	

ABB Limited

Measurement & Analytics Howard Road, St. Neots Cambridgeshire, PE19 8EU, UK Tel: +44 (0)1480 475 321 Fax: +44 (0)1480 217 948 Email: instrumentation@gb.abb.com

abb.com/measurement

ABB Limited Measurement & Analytics 125 E. County Line Road, Warminster, PA 18974 USA Tel: +1 215 674 6000 Fax: +1 215 674 7183

Any other comments

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not accept any responsibility whatsoever for potential errors or possible lack of information in this document. We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB. ©ABB 2018